

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	11MAY2015	DW	CW
	A1	ECR-17-018349	14DEC2017	DW	CW

NOTES:

1. TECHNICAL CHARACTERISTICS:

CONTACT MATERIAL: BRASS

SURFACE PLATING:

SILVER PLATING: $\geq 2\mu\text{m}$ CONTACT RESISTANCE: $\leq 0.5\text{m}\Omega$ WIRE RANGE: 25 mm²

OPERATION TEMPERATURE: -40~+125°C

注释:


1. 技术参数:

公针材料: 黄铜

表面电镀:

镀银: $\geq 2\mu\text{m}$ 接触电阻: $\leq 0.5\text{m}\Omega$ 接线范围: 25 mm²

工作温度: -40~+125°C

T2060001025-000	CHM-25	CHM-25, SILVER PLATING HMN-001公针 25mm ² , 镀银	25	19
PART NUMBER 料号	PART DESCRIPTION 描述		WIRE GAUGE (mm ²) 线规 (mm ²)	STRIPPING LENGTH (mm) 剥线长度 (mm)
THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 11MAY2015 David Wang	 TE Connectivity CHM-25 HM PIN CONTACT	
DIMENSIONS: mm		CHK 11MAY2015 Chris Wang		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD 11MAY2015 Xiang Xu		
0 PLC ±- 1 PLC ±- 2 PLC ±- 3 PLC ±- 4 PLC ±- ANGLES ±-		PRODUCT SPEC 108-137057		
MATERIAL	FINISH	APPLICATION SPEC 114-137057	SIZE	CAGE CODE
-	-	WEIGHT	A3	00779
-	-	Customer Drawing	DRAWING NO T2060001025000	
SCALE 2:1			SHEET 1 OF 1	REV A1

1470-19 (3/13)