



4:1 Shrinkable Polyolefin Tubing Flexible · Dual Wall

Smaller Sizes



Description: DAFLEX SM278 is a flexible, large ratio, heat shrinkable tubing with a meltable adhesive liner. When 120°C is applied, the tubing will shrink to 25% of its supplied size (4:1). Longitudinal shrinkage is 10% maximum. As the outer wall shrinks, the inner adhesive liner melts and flows. When cooled, it offers protection for a variety of electrical applications as well as "sealed-in" protection from chemicals and oils.

Because of its large shrink ratio and adhesive liner it offers excellent protection for cable repairs and retrofitting.

Operating Temperature: -55°C to +135°C.

Meets or exceeds MIL-I-23053/4 Class 3.

UL VW-1, CSA OFT (outer wall only).

Daburn Cat. No.	Nom. Size	Expanded ID		Recovered ID		Min. Rec. Wall		Standard Put-Up	Click to Order Prototype Quantities
		IN.	mm	IN.	mm	IN.	mm		
SM278-3/16	3/16	.157	4	.039	1	.0354	.90	200ft Spl*	Order
SM278-5/16	5/16	.315	8	.079	2	.0354	.90	100ft Spl**	Order
SM278-1/2	1/2	.472	12	.118	3	.0512	1.30	400ft 4ft lgths	Order
SM278-3/4	3/4	.630	16	.157	4	.0630	1.60	200ft 4ft lgths	Order
SM278-1"	1"	.945	24	.236	6	.0827	2.10	100ft 4ft lgths	Order
SM278-1 1/4"	1 1/4"	1.260	32	.315	8	.0906	2.30	80ft 4ft lgths	Order

Standard Color: Black. Clear and other colors are available to order.

Standard Package: *1000FT, **600FT. All others Standard Package shown.

To additional [Heat Shrinkable Tubing](#).

To [Heat Shrinkable Tubing Cross Reference](#) Property Chart.

Back to DABURN'S [Home Page](#).

Daburn electronics & cable corp.
224 Pegasus Ave.
Northvale, NJ 07647

Tel: 201-768-5400

Fax: 201-768-9642

E-Mail: daburn@daburn.com

URL: <http://www.daburn.com/>