



- NOTES :
- ▲ MATERIALS AND FINISH:
 - HOUSING: PA66
 - CONTACTS: BRASS, FINISH: TIN OVER NICKEL UNDERPLATE
- MUST COMPLY WITH DIRECTIVE 2002/95/EC (ROHS)
 - WIRE TYPES AND SIZES ACCEPTED
 WIRE RANGE: 20AWG~28AWG.
 STRIP LENGTH: 5.5mm~6.5mm
 - PACKAGED IN TRAY.
 - CURRENT RATING: 4Amp AC150V.
 - OPERATION TEMPERATURE: -40°C TO +105°C
 - THIS PART NO. IS THE SAME STRUCTURE AS THE SERIES: 2834085
 - THE DATASHEET AND MORE DETAILS PLEASE FOLLOW THE SERIES: 2834085

④	③	②	①	NO. OF POSITIONS	PART NO
WIRE PROTECTOR	CONTACT	COVER	HOUSING	A	
21.82	8 POSN	2834085-7			
19.28	7 POSN	2834085-6			
16.74	6 POSN	2834085-5			
14.20	5 POSN	2834085-4			
11.66	4 POSN	2834085-3			
9.12	3 POSN	2834085-2			
6.58	2 POSN	2834085-1			
A					

THIS DRAWING IS A CONTROLLED DOCUMENT.

STI TE Connectivity

254 45Entry Screwless Connector

DATE: 08DEC2015
 REV: 1

SIZE: A2
 CODE: 00779
 C-2834085

SCALE: 1:1

REV: A