


P1	P2
1 WHITE	6
2 BLACK	5
3 RED	4
4 GREEN	3
5 YELLOW	2
6 BLUE	1

Note:

- Material: Housing-polycarbonate, clear Terminal-0.36[.014] thick phosphor bronze. Thick gold in localized gold plate. Area, Gold Flash over the remainder. Over 2.54mm[.000100] thick nickel underplate.



Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length
AT-S-26-6/6/B-5	A	1,525±20(5ft)	Black	1,525-1,535mm
AT-S-26-6/6/B-7	B	2,135±30(7ft)	Black	2,135-2,145mm
AT-S-26-6/6/B-10	C	3,050±60(10ft)	Black	3,050-3,060mm
AT-S-26-6/6/B-12	D	3,660±60(12ft)	Black	3,660-3,670mm
AT-S-26-6/6/B-14	E	4,270±60(14ft)	Black	4,270-4,280mm
AT-S-26-6/6/B-25	F	7,625±100(25ft)	Black	7,625-7,635mm
AT-S-26-6/6/B-50	G	15,250±150(50ft)	Black	15,250-15,260mm



Scale	Free								
TOLERANCE									
X.	±X								
X.X	±X								
X.XX	±X								
DIM	TOL								
X.°	±X°								
X.X°	±X°								
Angle	TOL	Id.	Modification	Date	Name				



Title	Date	Name
Modular cable - Straight 6P6C 50µ", 26AWG, Black, 5-50 feet	08.07.13	Wilson
ASSMANN WSW-No.	08.07.13	Groll
AT-S-26-6/6/B-xx		
Drawing-No.		
Replace		
Sheet		
1/1		

rev00