

RJ Connectors

1 - 2 3 4 5 6 - 7 8 9

Specification

(RCP) RJ45 C Size (Plastic)
 (RCM) RJ45 C Size (Metal)
 (RDP) RJ45 D Size (Plastic)
 (RDM) RJ45 D Size (Metal)
 (ROP) RJ45 ODVA (Plastic)

Cat Type & Shielded

(00) None (5S) Cat.5e shielded
 (5U) Cat.5e Unshielded

Connector Body (Style)

> For Receptacle > For Overmolded with Cable
 (P) Front Fastened (A) With Strain Relief
 (R) Rear Fastened (B) Without Strain Relief
 (D) Dual Fastened
 > For Field Installable
 (A) With Strain Relief
 (B) Without Strain Relief

Connector (Housing) Gender

(MM) Plug (FF) Jack

Assemble Style

> For Receptacle > For Overmolded with Cable
 (H) Jack 180 (Horizontal) (M) Overmolded with Cable
 (V) Jack 90 (Vertical)
 > For Field Installable
 (A) Field installable (Compled)
 (S) Field installable (Feed-Thru)

Mating Style

(T) 3 Points Lock Bayonet (S) Screw Thread

Backshell

> For Receptacle > For Overmolded with Cable > For Field Installable
 (C) Circular (L) Straight (L) Straight
 (S) Square (R) Right Angle

Waterproof Types

(U) Unmated Waterproof (M) Mated Waterproof

Waterproof Rating

(7) IP 67 *IP 68 upon request.

More information

> For Receptacle > For Overmolded with Cable
 (001), (002)..... (□)+(■) : Cable Type + Cable Length
 (□) : Cable Type (■) : Cable Length
 (A) C5e UTP Solid Cable From 1M to 99M
 (B) C5e FTP Solid Cable EX. (01) = 1M

RJ Connector: Overmolded with Cable (Double-ended)
Waterproof to Waterproof / Non-Waterproof

Specification (1st End)

- (RCP) RJ45 C Size (Plastic)
- (RCM) RJ45 C Size (Metal)
- (RDP) RJ45 D Size (Plastic)
- (RDM) RJ45 D Size (Metal)
- (ROP) RJ45 ODVA (Plastic)

Cat Type & Shielded (1st End)

- (5U) Cat.5e Unshielded
- (5S) Cat.5e Shielded

Connector (Housing) Gender (1st End)

- (M) Plug
- (F) Jack

Specification (2nd End)

> For Waterproof Connectors

- (RCP) RJ45 C Size (Plastic)
- (RCM) RJ45 C Size (Metal)
- (RDP) RJ45 D Size (Plastic)
- (RDM) RJ45 D Size (Metal)
- (ROP) RJ45 ODVA (Plastic)

> For Non-Waterproof Plug

- (UPG) Unshielded Plug
- (SPG) Shielded Plug

Cat Type & Shielded (2nd End)

> For Waterproof Connectors

- (5U) Cat.5e Unshielded
- (5S) Cat.5e Unshielded

> For Non-Waterproof Plug

- (06) Gold Plating 6u"

Connector (Housing) Gender (2nd End)

- (M) Plug

Mating Style

- (T) 3 Points Lock Bayonet
- (S) Screw Thread

Backshell

> For Overmolded with Cable

- (L) Straight
- (R) Right Angle

More information

> For Overmolded with Cable

(□)+(■) : Cable Type + Cable Length

(□) : Cable Type (■) : Cable Length

(A) C5e UTP Solid Cable From 1M to 99M

(B) C5e FTP Solid Cable EX. (01) = 1M