



T-handle TorqueControl Tools



Includes Calibration Certificate



289 TorqueFix T-handle

EN ISO 6798, BS EN 26789, ASME B107.14M, +/- 6% Accuracy
Ergonomic multi-component handle, light and compact.

With Certificate of calibration.

Item No.	Torque		mm x mm	lbs. pkg.	
	In-lbs.	Nm		lbs.	pkg.
289 31	53.1	6	56 x 120	.81	1
289 33	70.8	8	56 x 120	.82	1
289 35	88.5	10	56 x 120	.79	1
289 37	106.2	12	56 x 120	.79	1
289 38	110.6	12.5	56 x 120	.80	1
289 39	123.9	14	56 x 120	.80	1

Each TorqueFix T-handle has unique serial number and certificate of calibration



289 TORX® Interchangeable Blades For TorqueFix T-Handle

TORX® tip blades on 6mm Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, hard chromed.

Item No.	Size	mm	Inch	mm	lbs.	pkg.
289 03	T15	130	5.1	4.0	.07	1
289 04	T20	130	5.1	4.0	.07	1
289 05	T25	130	5.1	4.0	.07	1
289 06	T27	130	5.1	4.0	.07	1
289 07	T30	130	5.1	4.0	.07	1
289 08	T40	130	5.1	4.0	.07	1



289 TORXPlus® Interchangeable Blades For TorqueFix T-Handle

TORXPlus® tip blades on 6mm Hex shafts. High alloy chrome-vanadium-molybdenum steel, hardened, hard chromed.

Item No.	Size	mm	Inch	mm	lbs.	pkg.
289 10	IP15	130	5.1	4.0	.07	1
289 11	IP20	130	5.1	4.0	.07	1
289 12	IP25	130	5.1	4.0	.07	1
289 13	IP27	130	5.1	4.0	.07	1
289 14	IP30	130	5.1	4.0	.07	1
289 15	IP40	130	5.1	4.0	.07	1



289 TorqueFix Adapter For 1/4" & 3/8" Sockets

Shaft CVM steel, hardened, corrosion protected.

Item No.	Size	mm	Inch	mm	lbs.	pkg.
289 26	1/4	100	3.9	6.0	.12	1
289 27	3/8	100	3.9	6.0	.15	1



See pages
211-215
for Sockets



289 Hex Metric Interchangeable Blades For TorqueFix T-Handle

Hex tip blades on 6mm Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item No.	mm	mm	Inch	lbs.	pkg.
289 16	3.0	130	5.1	.07	1
289 17	4.0	130	5.1	.07	1
289 18	5.0	130	5.1	.07	1
289 19	6.0	130	5.1	.07	1



289 25 TorqueFix Quick Release Bit Holder

Shaft CVM steel, hardened, corrosion protected.

Item No.	Size	mm	Inch	mm	lbs.	pkg.
289 25	1/4	125	4.9	6.0	.15	1



See pages
185-197
for Insert bits



289 Hex Inch Interchangeable Blades For TorqueFix T-Handle

Hex tip blades on 6mm Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item No.	Inch	mm	Inch	lbs.	pkg.
289 20	1/8	130	5.1	.07	1
289 21	9/64	130	5.1	.07	1
289 22	5/32	130	5.1	.07	1
289 23	3/16	130	5.1	.07	1
289 24	7/32	130	5.1	.07	1

See T-handles On Pages 25-26, 30, 47-50