



注記
NOTES

- 適合ハウジング:51154-160*, 501598-1604
APPLICABLE HOUSING:51154-160* . 501598-1604
- 材料:リン青銅、錫メッキ材 (t=0.2)
MATERIAL:PRE-TINNED PHOSPHOR BRONZE(t=0.2)
- 適用電線:APPLICABLE WIRE RANGE
AVS-0.5,AVS-0.5f,AVSS-0.5,AVSS-0.5f,CAVS-0.5,CAVUS-0.5
AVS-0.75f,AVSS-0.75f
AVS-0.85,AVSS-0.85,CAVS-0.85,CAVUS-0.85
- 被覆外径 Ø1.3-2.3
INS. RANGE

50695-8000	連鎖状 CHAIN
MATERIAL NO.	端子形状 FORM
MODEL NO.	50695-8*00

REVISED EC NO: J2009-1355 DRWN:NAKAMURA 2008/12/16 CHKD:T. HARUYAMA 2008/12/16 APPR:NUKITA 2009/01/14	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY	SCALE 5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
		10 UNDER	±0.2	DRAWN BY MSAKANO	DATE '96/11/28	TITLE 4.0 WIRE RO WIRE CRIMP RECEPTACLE		
		10 OVER 30 UNDER	±0.25	CHECKED BY MSAKANO	DATE '96/11/28	MOLEX INCORPORATED		
		30 OVER	±0.3	APPROVED BY MENOMOTO	DATE '96/11/28	MATERIAL NO.	DOCUMENT NO. SD-50695-001	SHEET NO. 1 OF 1
	REV	ANGULAR ±3 ° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			